

INDUSTRIAL / WAREHOUSE / MANUFACTURING

Better Light for Demanding Spaces.

HIGH-BAY LUMINAIRES



HXB SERIES

- 35,000 and 70,000 lumens
- Up to 150 LPW
- Input Power: 276W – 485W
- Operating temperature: -40°C to +60°C
- Input Voltage: 120-277V (UL), 347-480V (UH)
- IP6X optics



KBL SERIES

- 20,900 or 27,500 lumens
- Up to 150 LPW
- Input Power: 142W – 189W
- Operating temperature: -40°C up to 50°C
- Input Voltage: 120-277V (UL), 347-480V (UH)
- IP65 optical assembly
- Onboard emergency battery backup



LXB SERIES

- 12,000 to 60,000 lumens
- Up to 162 LPW
- Input Power: 80 - 365W
- Operating temperature: from -30°C to 55°C (-22°F to +131°F)
- Input Voltage: 120-277V



C-LITE™ ROUND HIGH-BAY

- 7,600 to 30,000 lumens
- Up to 130 LPW
- Input Power: 60 - 232W
- Operating temperature: from -30°C to 50°C (-22°F to +122°F)
- Input Voltage: 120-277V (UL), 347-480V (UH)

VAPOR TIGHT LUMINAIRES



WS SERIES - WS4-C

- 4,100 or 6,100 lumens
- Up to 142 LPW
- IP65 and IP66 rated for indoor and covered wet locations
- NSF Splash Zone II certified
- Diffused acrylic or polycarbonate lenses



C-LITE™ LINEAR

- 5,200 lumens
- Up to 130 LPW
- Input Power: 40W
- Operating temperature: -20°C to 45°C (-4°F to +113°F)
- Input Voltage: 120V-277V

STRIP LUMINAIRES

LSQ SQUARE AND LS SERIES

- 2,500 to 10,000 lumens
- Up to 157 LPW
- Three optic lens options: Lambertian, Aisle Lighter, Asymmetric Wall Wash
- 4' and 8' sizes
- Fully luminous with no pixelation

