



Photometry

All published luminaire photometric testing performed to IES LM-79-08 standards. To obtain an IES file specific to your project consult: <http://creelighting.com/products/outdoor/canopy-and-soffit/228-series>

SL



RESTL Test Report #: PL05297-001
CAN-228-SL-**-06-E-UL-700-40K
Initial Delivered Lumens: 13,102




SFT-228-SL-**-03-E-UL-350-IC-40K
Mounting Height: 15' (4.6m) A.F.G.
Initial Delivered Lumens: 3,635
Initial FC at grade


Sparkle Petroleum Distribution				
LED Count (x10)	4000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
350mA				
03	3,635	B2 U0 G1		B2 U0 G1

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

PS



RESTL Test Report #: PL05295-001
CAN-228-PS-**-06-E-UL-700-40K
Initial Delivered Lumens: 13,753



SFT-228-PS-**-03-E-UL-350-IC-40K
Mounting Height: 15' (4.6m) A.F.G.
Initial Delivered Lumens: 3,757
Initial FC at grade

Petroleum Distribution				
LED Count (x10)	4000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
350mA				
03	3,757	B2 U0 G0	3,902	B2 U0 G0

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens
** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

RR Mount

