

OOLV.E330248 - Lamps, Self-ballasted, Light-emitting-diode Type

Note: We are enhancing our systems and you may notice missing/outdated data. During this interim period, please refer to your Certificate of Compliance or contact our Customer Service at <https://www.ul.com/about/locations>.

Lamps, Self-ballasted, Light-emitting-diode Type

See General Information for Lamps, Self-ballasted, Light-emitting-diode Type

IDEAL INDUSTRIES LIGHTING LLC, DBA CREE LIGHTING

4401 SILICON DRIVE
DURHAM, NC 27703 USA

E330248

Trademark and/or Tradename:    
 

LED lamps, Model(s) BA19-04527#

LED Lamps, Model(s) BA19-04527OMB-xxxxxx-3

LED lamps, Model(s) BA19-04527OMF, BA19-04527OMF-xxxxxx-3

LED Lamps, Model(s) BA19-04527OMN

LED lamps, Model(s) BA19-04550 #

LED Lamps, Model(s) BA19-04550OMB-xxxxxx-3

LED lamps, Model(s) BA19-04550OMF, BA19-04550OMF-xxxxxx-3, BA19-08027#

LED Lamps, Model(s) BA19-08027OMB-xxxxxx-3

LED lamps, Model(s) BA19-08027OMF, BA19-08050OMF, BA19-08027OMF-xxCxxx-1, BA19-08027OMF-xxxxxx-3

LED Lamps, Model(s) BA19-08027OMN

LED lamps, Model(s) BA19-08050#

LED Lamps, Model(s) BA19-08050OMB-xxxxxx-3

LED lamps, Model(s) BA19-08050OMF-xxCxxx-1, BA19-08050OMF-xxxxxx-3

LED Lamps, Model(s) BA19-11027

LED lamps, Model(s) BA19-11027OMF-xxxxxx-2 (a), BA19-11050 #, BA19-11050OMF-xxxxxx-2 (a), BA21-16027OMF-xxDxx-1, BA21-16050OMF-xxDxx-1, BA21-16027OMF-xxDxx-2, BA21-16027OMF-xxWxx-1, BA21-16027OMF-xxWxx-2, BA21-16050OMF-xxDxx-2, BA21-16050OMF-xxWxx-1, BA21-16050OMF-xxWxx-2, BB13-02027OMC-xxxxxx-1Cxxx, BB13-03527OMC-xxxxxx-1Cxxx, BBR30-06527xxF-xxxxxx-1, BBR30-06527xxF-xxxxxx-3, BBR30-06550xxF-xxxxxx-3, BBR30-06527xxF-xxxxxx-4, BBR30-06527xxN-xxxxxx-3, BBR30-06527xxx-xxxx-1 (-2 or -3) \$, BBR30-06550xxF-xxxxxx-1, BBR30-06550xxF-xxxxxx-4, BBR40-07627xxx-xxxxxx-1, BBR40-07650xxx-xxxxxx-1, BPAR30L-xxxxxxx-xxxxxx-1(a), BPAR30S-xxxxxxx-xxxxxx-1(a), BPAR38-xxxxxxx-xxxxxx-1\$, BPAR38-xxxxxxx-xxxxxx-2\$, LBR30*, LM16-35-xxK-dd (@), LM16-50-xxK-dd (@), LRP38*

LED lamps, Model(s) LRP38-10L-xxK-zzD-yyyy where 'xx' and 'zz' are any alphanumeric not related to safety, and 'yyyy' is blank or 'GU24'

LED lamps, Model(s) LRP38-10L-xxK-zzD-yyyy-ND where 'xx' and 'zz' are any alphanumeric not related to safety, and 'yyyy' is blank or 'GU24'

LED lamps, Model(s) LRP38-14L-xxK-zzD-yyyy-ND, where 'xx' and 'zz' are any alphanumeric not related to safety, and 'yyyy' is blank or 'GU24'

LED lamps, Model(s) MR16-50W-30K-xxD, SA19-04627MDFD-XXXXXX-1-XXX(b), SA19-04650MDFD-XXXXXX-1-XXX(b), SA19-08127MDFD-XXXXXX-1-XXX(b), SA19-08150MDFD-XXXXXX-1-XXX(b), SA19-11027XXX-XXXXXX-1-XXX, SA19-11050XXX-XXXXXX-1-XXX, SA21-16027XXX-XXDXXX-1-XXX, SA21-16027XXX-XXWXXX-1-XXX, SA21-16050XXX-XXDXXX-1-XXX, SB13-02427MDCH-xxxxxx-1xxx (a), SB13-03427MDCH-xxxxxx-1xxx (a), SBR30-06527FLFD-XXXXXX-1-XXX (b), SBR30-06550FLFD-XXXXXX-1-XXX (b), SPAR30L-xxxxxxx-xxxxx-1, SPAR30S-xxxxxxx-xxxxx-1

Self-Ballasted Lamps, Model(s) C-BR30-A-65W-DIM-XXK (d)

Self-Ballasted Lamps, LED type, Model(s) A19-40W-P1-XXK-E26 (d), A19-60W-B1-XXK-E26, A19-60W-P1-27K-E26, A19-60W-P1-30K-E26, A19-60W-P1-40K-E26, A19-60W-P1-50K-E26, A19-60W-P1-XXK-E26 (d), A19-75W-P1-XXK-E26 (d), A21-100W-P1-XXK-E26 (d), A21-3WAY-P1-XXK-E26 (d), BR30-100W-P1-27K-E26, BR30-100W-P1-30K-E26, BR30-100W-P1-50K-E26, BR30-100W-P1-XXK-E26 (d), BR30-65W-B1-XXK-E26-U2, BR40-120W-P1-XXK-E26 (d)

Self-Ballasted Lamps, LED type, Model(s) C-A19-A-40W-DIM-XXK, C-A19-A-60W-DIM-XXK, C-A19-A-75W-DIM-XXK

Self-Ballasted Lamps, LED type, Model(s) C-A19-A-40W-ND-XXK (a), C-A19-A-60W-ND-XXK (a), C-A19-A-75W-ND-XXK (a), PAR38-150W-P1-30K-40FL-E26-U1, PAR38-150W-P1-XXK-YYFL-E26 (c), R20-50W-P1-XXK-E26 (d), R20-75W-P1-XXK-E26 (d), SB13-05027MDCH-xxxxxx-1xxx, SBR30-065XXFLFH-12DE26-Z (n), SBR30-15027FLFH-XXXXXX-1-XXX, SBR30-15030FLFH-XXXXXX-1-XXX, SBR30-15035FLFH-XXXXXX-1-XXX, SBR30-15040FLFH-XXXXXX-1-XXX, SBR30-15050FLFH-XXXXXX-1-XXX, SBR40-110XXFLFD-12DE26-1 (@), SBR40-110YYFLFD-12DE26-1 (@), SPAR38-150XXYYTD-12DE26-1, TA19-045XXMDFH25-12DE26-1 (d), TA19-08027MDFH25-12DE26-1, TA19-08030MDFH25-12DE26-1, TA19-08050MDFH25-12DE26-1, TA19-080XXMDFH25-12DE26-1 (d), TA19-110XXMDFH25-12DE26-1 (d), TA21-150XXMDFH25-12WE26-1 (d), TA21-160XXMDFH25-12DE26-1 (d), TBR30-06527FLFH25-12DE26-1, TBR30-06530FLFH25-12DE26-1, TBR30-06550FLFH25-12DE26-1, TBR30-065XXFLFH25-12DE26-1 (d), TBR30-14027FLFH25-12DE26-1, TBR30-14030FLFH25-12DE26-1, TBR30-14050FLFH25-12DE26-1, TBR30-140XXFLFH25-12DE26-1 (d), TBR40-180XXFLFH25-12DE26-1 (d), TPAR38-150XXYYFH25-12DE26-1 (c), TPAR38-180XXYYFH25-12DE26-1 (c), TR20-070XXFLFH25-12DE26-1 (d), TR20-098XXFLFH25-12DE26-1 (d), YGA08A63-BR30-8.8W-9XX-Z (n)

Self-Ballasted LED Lamps, Model(s) SBR40-18027FLFH-12DE26-1, SBR40-18030FLFH-12DE26-1, SBR40-18035FLFH-12DE26-1, SBR40-18040FLFH-12DE26-1, SBR40-18050FLFH-12DE26-1, SPAR20-0552740TH-12DE26-1, SPAR20-0553040TH-12DE26-1, SPAR20-0554040TH-12DE26-1, SR20-10027FLFH-12DE26-1, SR20-10030FLFH-12DE26-1, SR20-10035FLFH-12DE26-1, SR20-10040FLFH-12DE26-1, SR20-10050FLFH-12DE26-1, TPAR20-0553040FH25-12DE26-1

Self-ballasted light-emitting-diode (LED) lamps, Model(s) B11-25W-P1-XXK-E12 (d), B11-40W-P1-XXK-E12 (d), B11-60W-P1-XXK-E12 (d), TB11-018XXMDCH15-12DE12-1 (d), TB11-035XXMDCH15-12DE12-1 (d), TB11-050XXMDCH15-12DE12-1 (d)

Model(s) A19-100W-P1-27K-E26-U1, A19-100W-P1-30K-E26-U1, A19-100W-P1-50K-E26-U1, A19-60W-B2-27K-E26-U4, A19-60W-B2-50K-E26-U4, A21-125W-P1-27K-E26-U1, A21-125W-P1-30K-E26-U1, A21-125W-P1-50K-E26-U1, BR30-65W-B2-27K-E26-U2, BR30-65W-B2-50K-E26-U2, C-A19-A-60W-DIM-27K-GU24, C-A19-A-60W-DIM-30K-GU24, CMA19-60W-AL-827, CMA19-60W-AL-9ACK, CMA21-100W-AL-9ACK, CMBR30-65W-AL-9ACK, CMPAR38-120W-AL-9ACK, MR16-50W-P1-30K-35FL-GU10, MR16-50W-P1-30K-35FL-GU10-U1, MR16-75W-P1-27K-15SP-GU53-U1, MR16-75W-P1-27K-25NF-GU53-U1, MR16-75W-P1-27K-35FL-GU53-U1, MR16-75W-P1-30K-15SP-GU53-U1, MR16-75W-P1-30K-25NF-GU53-U1, MR16-75W-P1-30K-35FL-GU10, MR16-75W-P1-30K-35FL-GU10-U1, MR16-75W-P1-30K-35FL-GU53-U1

Model(s) MR16-75W-P1-XXK-15SP-GU53 Where XX can be any number to indicate color temperature.

Model(s) MR16-75W-P1-XXK-25NF-GU53 Where XX can be any number to indicate color temperature.

Model(s) MR16-75W-P1-XXK-35FL-GU53 Where XX can be any number to indicate color temperature.

Model(s) PAR20-50W-P1-27K-15SP-E26-U1, PAR20-50W-P1-27K-25NF-E26-U1, PAR20-50W-P1-27K-40FL-E26-U1, PAR20-50W-P1-30K-15SP-E26-U1, PAR20-50W-P1-30K-25NF-E26-U1, PAR20-50W-P1-30K-40FL-E26-U1, PAR20-50W-P1-40K-40FL-E26-U1

Model(s) PAR20-50W-P1-XXK-YYYY-E26 Where XX may be any number to indicate the color temperature and YYYY may be any number to indicate the beam angle.

Model(s) PAR30L-75W-P1-27K-15SP-E26-U1, PAR30L-75W-P1-27K-25NF-E26-U1, PAR30L-75W-P1-27K-40FL-E26-U1, PAR30L-75W-P1-30K-15SP-E26-U1, PAR30L-75W-P1-30K-25NF-E26-U1, PAR30L-75W-P1-30K-40FL-E26-U1, PAR30L-75W-P1-40K-40FL-E26-U1

Model(s) PAR30L-75W-P1-XXK-YYYY-E26 Where XX may be any number to indicate the color temperature and YYYY may be any number to indicate the beam angle.

Model(s) PAR30S-75W-P1-27K-15SP-E26-U1, PAR30S-75W-P1-27K-25NF-E26-U1, PAR30S-75W-P1-27K-40FL-E26-U1, PAR30S-75W-P1-30K-15SP-E26-U1, PAR30S-75W-P1-30K-25NF-E26-U1, PAR30S-75W-P1-30K-40FL-E26-U1, PAR30S-75W-P1-40K-40FL-E26-U1

Model(s) PAR30S-75W-P1-XXK-YYYY-E26 Where XX may be any number to indicate the color temperature and YYYY may be any number to indicate the beam angle.

Model(s) PAR38-120W-P1-27K-15SP-E26-U1, PAR38-120W-P1-27K-25NF-E26-U1, PAR38-120W-P1-27K-40FL-E26-U1, PAR38-120W-P1-30K-15SP-E26-U1, PAR38-120W-P1-30K-25NF-E26-U1, PAR38-120W-P1-30K-40FL-E26-U1, PAR38-120W-P1-40K-40FL-E26-U1

Model(s) PAR38-120W-P1-XXK-YYYY-E26 Where XX may be any number to indicate the color temperature and YYYY may be any number to indicate the beam angle.

Model(s) PAR38-250W-P1-30K-40FL-E26-U1, PAR38-90W-B2-30K-E26-U2, TA19-16027MDFH25-12DE26-1, TA19-16030MDFH25-12DE26-1, TA19-16050MDFH25-12DE26-1, TA21-20027MDFH25-12DE26-1, TA21-20030MDFH25-12DE26-1, TA21-20050MDFH25-12DE26-1, TB11-03527MDCH25-12DE12-1, TB11-03550MDCH25-12DE12-1, TB11-05027MDCH25-12DE12-1, TB11-05050MDCH25-12DE12-1, TB11-07027MDCH25-12DE12-1, TB11-07027MDCH25-12DE26-1, TB11-07050MDCH25-12DE12-1, TPAR20-0553040FH25-12DE26-2, TPAR38-1503025FH25-12DE26-1, TPAR38-1503025FH25-12DE26-1-11003S-T, TPAR38-1503040FH25-12DE26-1, TPAR38-1503040FH25-12DE26-1-11003S-T, TPAR38-1504040FH25-12DE26-1, TPAR38-1803040FH25-12DE26-1, TPAR38-1803040FH25-12DE26-1-11003S-T, TPAR38-1805040FH25-12DE26-1, TPAR38-1805040FH25-12DE26-1-11003S, TPAR38-2203040FH25-12DE26-1, TPAR38-2205040FH25-12DE26-1, TR20-14027FLFH25-12DE26-1, TR20-14050FLFH25-12DE26-1

- The model numbers stated may be followed by additional alphanumeric characters not related to safety.

\$ - Where the x employed within the model designation can be any multiple of alphanumeric characters. The model numbers stated may be followed by additional alphanumeric characters not related to safety.

(@) - Where "XX" and "YY" can be any two-digit number which represents color temperature, and "XX" is more than "40" or equal to "40", "YY" is less than "40".

(a) - "x" may be any alphanumeric characters.

(b) - The series of "x" following the model numbers may be any additional alphanumeric characters not related to safety

(c) - Where XX may be any number to indicate the color temperature and YY may be any number to indicate the beam angle.

(d) - Where XX may be any number to indicate the color temperature.

(n) - Where "XX" may be any number indicates the color temperature; "Z" is "1-6" or blank represents different LED manufacture.

* - With or without additional suffixes and/or part designations.

@ - where 'xx' and/or 'dd' are any alphanumeric not related to safety. (*)

A - Where suffix A represents the LED type

ZZ - the first "Z" means the CCT (2700K, 3000K, 4000K, 5000K,6500K), the second "Z" means the shape of diffuser.

Last Updated on 2020-07-25

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"