

# IFAM7.E329322 - LIGHT-EMITTING-DIODE SURFACE-MOUNTED LUMINAIRES CERTIFIED FOR CANADA

## Light-emitting-diode Surface-mounted Luminaires Certified for Canada

See General Information for Light-emitting-diode Surface-mounted Luminaires Certified for Canada

### CREE INC

E329322

4600 SILICON DR  
DURHAM, NC 27703-8475 USA

**LED Luminaires, Surface-Mounted, Wet Location**, Model(s) C-AR-A-DD-5L-40K-GR, C-AR-A-DD-5L-50K-GR, C-WM-A-WLAR-11L-50K-MB, C-WP-A-SL-16L-40K-DB, C-WP-A-SL-16L-50K-DB, C-WP-A-SL-4L-40K-DB, C-WP-A-SL-4L-50K-DB, C-WP-A-SL-8L-40K-DB, C-WP-A-SL-8L-50K-DB, E-WF1L04CZ, E-WF1L04NZ, E-WF1L06CZ, E-WF1L06NZ, E-WF2L08CZ, E-WF2L08NZ, E-WF2L15CZ, E-WF2L15NZ, S-WPSLX, S-WPSSX may be SFS, SFB, TR or W

**LED Pendant Surface-Mounted Luminaires, suitable for damp locations**, Model(s) C-LB-A-RDAC-8L-40K-WH, C-LB-A-RDAC-8L-50K-WH, C-LB-A-RDAL-8L-40K-WH, C-LB-A-RDAL-8L-50K-WH

**LED Pole/Post Mounted Luminaire**, Model(s) OSQ HO Series Additional characters may be added to the model designation.

**LED surface mount canopy lights**, Model(s) BXCL or XCL or CAN-EDG

**LED Surface Mounted Luminaire, "Strip Lighting"**, Model(s) C-STRIP-A-LIN2-12L-30K-WH, C-STRIP-A-LIN2-12L-35K-WH, C-STRIP-A-LIN2-12L-40K-WH, C-STRIP-A-LIN2-13L-50K-WH, C-STRIP-A-LIN4-22L-30K-WH, C-STRIP-A-LIN4-23L-35K-WH, C-STRIP-A-LIN4-23L-40K-WH, C-STRIP-A-LIN4-25L-50K-WH, C-STRIP-A-LIN4-43L-30K-WH, C-STRIP-A-LIN4-44L-35K-WH, C-STRIP-A-LIN4-46L-40K-WH, C-STRIP-A-LIN4-49L-50K-WH, C-WR-A-WLIN2-24L-30K-WH, C-WR-A-WLIN2-24L-35K-WH, C-WR-A-WLIN2-24L-40K-WH, C-WR-A-WLIN2-24L-50K-WH, C-WR-A-WLIN4-48L-30K-WH, C-WR-A-WLIN4-48L-35K-WH, C-WR-A-WLIN4-48L-40K-WH, C-WR-A-WLIN4-48L-50K-WH

**LED Surface Mounted Luminaire, "WS4C"**, Model(s) WS4C

**LED Surface Mounted Luminaire**, Model(s) BRSWL, BRSWS, BXSP, C-AR-A-ARR3-50L-50K-UH-DB, C-AR-A-ARR3-50L-50K-UL-DB, C-AR-A-ARR5-50L-50K-UH-DB, C-AR-A-ARR5-50L-50K-UL-DB, C-AR-A-SQT3-16L-40K-DB, C-AR-A-SQT3-17L-50K-DB, C-AR-A-SQT5-15L-50K-DB, C-AR-A-SQT5-16L-40K-DB, C-AR-A-SQT7-17L-40K-DB, C-AR-A-SQT7-17L-50K-DB, C-PHB-B-L2F-14L-40K-WH-C, C-PHB-B-L2F-14L-40K-WH-D, C-PHB-B-L2F-14L-50K-WH-C, C-PHB-B-L2F-14L-50K-WH-D, C-PHB-B-L2F-15L-40K-UL-WH, C-PHB-B-L2F-15L-50K-UL-WH, C-PHB-B-L2F-21L-40K-WH-C, C-PHB-B-L2F-21L-40K-WH-D, C-PHB-B-L2F-21L-50K-WH-C, C-PHB-B-L2F-21L-50K-WH-D, C-PHB-B-L2F-22L-40K-UL-WH, C-PHB-B-L2F-22L-50K-UL-WH, C-PHB-B-L2F-30L-40K-UL-WH, C-PHB-B-L2F-30L-40K-UL-WH-D, C-PHB-B-L2F-30L-50K-UL-WH, C-PHB-B-L2F-30L-50K-UL-WH-D, C-PHB-B-L4F-30L-40K-UL-WH, C-PHB-B-L4F-30L-40K-WH-C, C-PHB-B-L4F-30L-40K-WH-D, C-PHB-B-L4F-30L-50K-UL-WH, C-PHB-B-L4F-30L-50K-WH-C, C-PHB-B-L4F-30L-50K-WH-D, C-PHB-B-L4F-43L-40K-UL-WH, C-PHB-B-L4F-43L-40K-WH-C, C-PHB-B-L4F-43L-40K-WH-D, C-PHB-B-L4F-43L-50K-UL-WH, C-PHB-B-L4F-43L-50K-WH-C, C-PHB-B-L4F-43L-50K-WH-D

**LED Surface Mounted Luminaire**, Model(s) C-VT-A-LIN4-52L-XXK-GR Where XX Refers to 40 or 50 and means: CCT 4000K or 5000K.

**LED Surface Mounted Luminaire**, Model(s) C-VT-B-SMCL-10L-40K-GR, C-VT-B-SMCL-10L-50K-GR, C-VT-B-SMCL-19L-40K-GR, C-VT-B-SMCL-19L-50K-GR, C-VT-B-SMWL-10L-40K-GR, C-VT-B-SMWL-10L-50K-GR, C-VT-B-SMWL-19L-40K-GR, C-VT-B-SMWL-19L-50K-GR, C-WP-A-TR-12L-40K-DB, C-WP-A-TR-12L-50K-DB, C-WP-A-TR-13L-40K-DB, C-WP-A-TR-13L-50K-DB, C-WP-A-TR-15L-40K-DB, C-WP-A-TR-15L-50K-DB, C-WP-A-TR-16L-40K-DB, C-WP-A-TR-16L-50K-DB, C-WP-A-TR-21L-40K-DB, C-WP-A-TR-21L-50K-DB, C-WP-A-TRAD-4L-30K-DB, C-WP-A-TRAD-4L-40K-DB, C-WP-A-TRAD-4L-50K-DB

**LED Surface Mounted Luminaire**, Model(s) C-WP-A-TRADX where X = any alpha numeric character.

**LED Surface Mounted Luminaire**, Model(s) C-WP-B-TRAD-3L-30K-DB, C-WP-B-TRAD-3L-40K-DB, C-WP-B-TRAD-3L-50K-DB, CE-JB4-600L-xxK-E26-3, CE-JB6-650L-xxK-E26-3, CXBA Series, DS4-600L-xxK-U1, DS4-750L-xxK-U1, DS6-700L-xxK-U1, DS6-900L-xxK-U1

**LED Surface Mounted Luminaire**, Model(s) E-APAXX XX may be a combination of numbers or numbers and letters.

**LED Surface Mounted Luminaire**, Model(s) E-HLD14B-HK40UW, E-HLD14B-HK40UW-D, E-HLD14B-HK50UW, E-HLD14B-HK50UW-D, E-HLD21B-HK40UW, E-HLD21B-HK40UW-D, E-HLD21B-HK50UW, E-HLD21B-HK50UW-D, E-HLD30B-HK40UW, E-HLD30B-HK40UW-D, E-HLD30B-HK50UW, E-HLD30B-HK50UW-D, E-HLD43B-HK40UW, E-HLD43B-HK40UW-D, E-HLD43B-HK50UW, E-HLD43B-HK50UW-D

**LED Surface Mounted Luminaire**, Model(s) E-TDF03E-22RXXN where (x) can be any alpha numeric character that does not affect safety.

**LED Surface Mounted Luminaire**, Model(s) E-TDF04E-14RXXN where (x) can be any alpha numeric character that does not affect safety.

**LED Surface Mounted Luminaire**, Model(s) E-TDF04E-24RXXN where (x) can be any alpha numeric character that does not affect safety.

**LED Surface Mounted Luminaire**, Model(s) E-TDF05E-22RXXN where (x) can be any alpha numeric character that does not affect safety.

**LED Surface Mounted Luminaire**, Model(s) E-TDF05E-24RXXN where (x) can be any alpha numeric character that does not affect safety.

**LED Surface Mounted Luminaire**, Model(s) E-WP10L08CZ, E-WP10L08NZ, E-WP12L12UCZ, E-WP12L12UNZ, E-XB1L11YU, E-XB1L22YU

**LED Surface Mounted Luminaire**, Model(s) HXB-Bx where x = any combination of additional alpha-numeric characters

**LED Surface Mounted Luminaire**, Model(s) HXB-Cx where x = any combination of additional alpha-numeric characters

**LED Surface Mounted Luminaire**, Model(s) KBLx

**LED Surface Mounted Luminaire**, Model(s) LSw4C-25L-xxK-34-y-FD where w can be any letter or blank, xx can be any number and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw4C-25L-xxK-y-FD where w can be any letter or blank, xx can be any number and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw4C-40L-xxK-34-y-FD where w can be any letter or blank, xx can be any number and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw4C-40L-xxK-y-FD where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw4C-50L-xxK-34-y-FD where w can be any letter or blank, xx can be any number and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw4C-50L-xxK-y-FD where w can be any letter or blank, xx can be any number and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8-100L-xxK-y-FD where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8-80L-xxK-y-FD where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8C-100L-35K-y-FD where w can be any number or blank, and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8C-100L-40K-y-FD where w can be any number or blank and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8C-100L-50K-y-FD where w can be any number or blank and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8C-80L-35K-34-y-FD where w can be any number or blank and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8C-80L-35K-y-FD where w can be any number or blank and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8C-80L-40K-34-y-FD where w can be any number or blank and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8C-80L-40K-y-FD where w can be any number or blank and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8C-80L-50K-34-y-FD where w can be any number or blank and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LSw8C-80L-50K-y-FD where w can be any number or blank and (y) can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED Surface Mounted Luminaire**, Model(s) LXB-A-12L-40K-8-UL-10V, LXB-A-12L-50K-8-UL-10V, LXB-A-18L-40K-8-UL-10V, LXB-A-18L-50K-8-UL-10V, LXB-A-24L-40K-8-UL-10V, LXB-A-24L-50K-8-UL-10V, LXB-A-28L-40K-8-UL-10V, LXB-A-28L-50K-8-UL-10V, LXB-A-40L-40K-8-UL-10V, LXB-A-40L-50K-8-UL-10V, LXB-A-60L-40K-8-UL-10V, LXB-A-60L-50K-8-UL-10V, NTA-A-NM-T3-11L-30K-UH-BZ, NTA-A-NM-T3-11L-30K-UL-BZ, NTA-A-NM-T3-11L-40K-UH-BZ, NTA-A-NM-T3-11L-40K-UL-BZ, NTA-A-NM-T3-11L-50K-UH-BZ, NTA-A-NM-T3-11L-50K-UL-BZ, NTA-A-NM-T3-11L-57K-UH-BZ, NTA-A-NM-T3-11L-57K-UL-BZ, NTA-A-NM-T3-19L-30K-UH-BZ, NTA-A-NM-T3-19L-30K-UL-BZ, NTA-A-NM-T3-19L-40K-UH-BZ, NTA-A-NM-T3-19L-40K-UL-BZ, NTA-A-NM-T3-19L-50K-UH-BZ, NTA-A-NM-T3-19L-50K-UL-BZ, NTA-A-NM-T3-19L-57K-UH-BZ, NTA-A-NM-T3-19L-57K-UL-BZ, NTA-A-NM-T3-35L-30K-UH-BZ, NTA-A-NM-T3-35L-30K-UL-BZ, NTA-A-NM-T3-35L-40K-UH-BZ, NTA-A-NM-T3-35L-40K-UL-BZ, NTA-A-NM-T3-35L-50K-UH-BZ, NTA-A-NM-T3-35L-50K-UL-BZ, NTA-A-NM-T3-35L-57K-UH-BZ, NTA-A-NM-T3-35L-57K-UL-BZ, NTA-A-NM-T4-11L-30K-UH-BZ, NTA-A-NM-T4-11L-30K-UL-BZ, NTA-A-NM-T4-11L-40K-UH-BZ, NTA-A-NM-T4-11L-40K-UL-BZ, NTA-A-NM-T4-11L-50K-UH-BZ, NTA-A-NM-T4-11L-50K-UL-BZ, NTA-A-NM-T4-11L-57K-UH-BZ, NTA-A-NM-T4-11L-57K-UL-BZ, NTA-A-NM-T4-19L-30K-UH-BZ, NTA-A-NM-T4-19L-30K-UL-BZ, NTA-A-NM-T4-19L-40K-UH-BZ, NTA-A-NM-T4-19L-40K-UL-BZ, NTA-A-NM-T4-19L-50K-UH-BZ, NTA-A-NM-T4-19L-50K-UL-BZ, NTA-A-NM-T4-19L-57K-UH-BZ, NTA-A-NM-T4-19L-57K-UL-BZ, NTA-A-NM-T4-35L-30K-UH-BZ, NTA-A-NM-T4-35L-30K-UL-BZ, NTA-A-NM-T4-35L-40K-UH-BZ, NTA-A-NM-T4-35L-40K-UL-BZ, NTA-A-NM-T4-35L-50K-UH-BZ, NTA-A-NM-T4-35L-50K-UL-BZ, NTA-A-NM-T4-35L-57K-UH-BZ, NTA-A-NM-T4-35L-57K-UL-BZ, NTA-A-NM-T5-11L-30K-UH-BZ, NTA-A-NM-T5-11L-30K-UL-BZ, NTA-A-NM-T5-11L-40K-UH-BZ, NTA-A-NM-T5-11L-40K-UL-BZ, NTA-A-NM-T5-11L-50K-UH-BZ, NTA-A-NM-T5-11L-50K-UL-BZ, NTA-A-NM-T5-11L-57K-UH-BZ, NTA-A-NM-T5-11L-57K-UL-BZ, NTA-A-NM-T5-19L-30K-UH-BZ, NTA-A-NM-T5-19L-30K-UL-BZ, NTA-A-NM-T5-19L-40K-UH-BZ, NTA-A-NM-T5-19L-40K-UL-BZ, NTA-A-NM-T5-19L-50K-UH-BZ, NTA-A-NM-T5-19L-50K-UL-BZ, NTA-A-NM-T5-19L-57K-UH-BZ, NTA-A-NM-T5-19L-57K-UL-BZ, NTA-A-NM-T5-35L-30K-UH-BZ, NTA-A-NM-T5-35L-30K-UL-BZ, NTA-A-NM-T5-35L-40K-UH-BZ, NTA-A-NM-T5-35L-40K-UL-BZ, NTA-A-NM-T5-35L-50K-UH-BZ, NTA-A-NM-T5-35L-50K-UL-BZ, NTA-A-NM-T5-35L-57K-UH-BZ, NTF-A-NM-N3-10L-30K-UH-BZ, NTF-A-NM-N3-10L-30K-UL-BZ, NTF-A-NM-N3-10L-40K-UH-BZ, NTF-A-NM-N3-10L-40K-UL-BZ, NTF-A-NM-N3-10L-50K-UH-BZ, NTF-A-NM-N3-10L-50K-UL-BZ, NTF-A-NM-N3-10L-57K-UH-BZ, NTF-A-NM-N3-10L-57K-UL-BZ, NTF-A-NM-N3-14L-30K-UH-BZ, NTF-A-NM-N3-14L-30K-UL-BZ, NTF-A-NM-N3-14L-40K-UH-BZ, NTF-A-NM-N3-14L-40K-UL-BZ, NTF-A-NM-N3-14L-50K-UH-BZ, NTF-A-NM-N3-14L-50K-UL-BZ, NTF-A-NM-N3-14L-57K-UH-BZ, NTF-A-NM-N3-14L-57K-UL-BZ, NTF-A-NM-N3-1L-30K-UH-BZ, NTF-A-NM-N3-1L-30K-UL-BZ, NTF-A-NM-N3-1L-40K-UH-BZ, NTF-A-NM-N3-1L-40K-UL-BZ, NTF-A-NM-N3-1L-50K-UH-BZ, NTF-A-NM-N3-1L-50K-UL-BZ, NTF-A-NM-N3-1L-57K-UH-BZ, NTF-A-NM-N3-1L-57K-UL-BZ, NTF-A-NM-N3-21L-30K-UH-BZ, NTF-A-NM-N3-21L-30K-UL-BZ, NTF-A-NM-N3-21L-40K-UH-BZ, NTF-A-NM-N3-21L-40K-UL-BZ, NTF-A-NM-N3-21L-50K-UH-BZ, NTF-A-NM-N3-21L-50K-UL-BZ, NTF-A-NM-N3-21L-57K-UH-BZ, NTF-A-NM-N3-21L-57K-UL-BZ, NTF-A-NM-N3-28L-30K-UH-BZ, NTF-A-NM-N3-28L-30K-UL-BZ, NTF-A-NM-N3-28L-40K-UH-BZ, NTF-A-NM-N3-28L-40K-UL-BZ, NTF-A-NM-N3-28L-50K-UH-BZ, NTF-A-NM-N3-28L-50K-UL-BZ, NTF-A-NM-N3-28L-57K-UH-BZ, NTF-A-NM-N3-28L-57K-UL-BZ, NTF-A-NM-N3-3L-30K-UH-BZ, NTF-A-NM-N3-3L-30K-UL-BZ, NTF-A-NM-N3-3L-40K-UH-BZ, NTF-A-NM-N3-3L-40K-UL-BZ, NTF-A-NM-N3-3L-50K-UH-BZ, NTF-A-NM-N3-3L-50K-UL-BZ, NTF-A-NM-N3-3L-57K-UH-BZ, NTF-A-NM-N3-3L-57K-UL-BZ, NTF-A-NM-N3-6L-30K-UH-BZ, NTF-A-NM-N3-6L-30K-UL-BZ, NTF-A-NM-N3-6L-40K-UH-BZ, NTF-A-NM-N3-6L-40K-UL-BZ, NTF-A-NM-N3-6L-50K-UH-BZ, NTF-A-NM-N3-6L-50K-UL-BZ, NTF-A-NM-N3-6L-57K-UH-BZ, NTF-A-NM-N3-6L-57K-UL-BZ, NTF-A-NM-N4-10L-30K-UH-BZ, NTF-A-NM-N4-10L-30K-UL-BZ, NTF-A-NM-N4-10L-40K-UH-BZ, NTF-A-NM-N4-10L-40K-UL-BZ, NTF-A-NM-N4-10L-50K-UH-BZ, NTF-A-NM-N4-10L-50K-UL-BZ, NTF-A-NM-N4-10L-57K-UH-BZ, NTF-A-NM-N4-10L-57K-UL-BZ, NTF-A-NM-N4-14L-30K-UH-BZ, NTF-A-NM-N4-14L-30K-UL-BZ, NTF-A-NM-N4-14L-40K-UH-BZ, NTF-A-NM-N4-14L-40K-UL-BZ, NTF-A-NM-N4-14L-50K-UH-BZ, NTF-A-NM-N4-14L-50K-UL-BZ, NTF-A-NM-N4-14L-57K-UH-BZ, NTF-A-NM-N4-14L-57K-UL-BZ, NTF-A-NM-N4-21L-30K-UH-BZ, NTF-A-NM-N4-21L-30K-UL-BZ, NTF-A-NM-N4-21L-40K-UH-BZ, NTF-A-NM-N4-21L-40K-UL-BZ, NTF-A-NM-N4-21L-50K-UH-BZ, NTF-A-NM-N4-21L-50K-UL-BZ, NTF-A-NM-N4-21L-57K-UH-BZ, NTF-A-NM-N4-21L-57K-UL-BZ, NTF-A-NM-N4-28L-30K-UH-BZ, NTF-A-NM-N4-28L-30K-UL-BZ, NTF-A-NM-N4-28L-40K-UH-BZ, NTF-A-NM-N4-28L-40K-UL-BZ, NTF-A-NM-N4-28L-50K-UH-BZ, NTF-A-NM-N4-28L-50K-UL-BZ, NTF-A-NM-N4-28L-57K-UH-BZ, NTF-A-NM-N4-28L-57K-UL-BZ, NTF-A-NM-N4-3L-30K-UH-BZ, NTF-A-NM-N4-3L-30K-UL-BZ, NTF-A-NM-N4-3L-40K-UH-BZ, NTF-A-NM-N4-3L-40K-UL-BZ, NTF-A-NM-N4-3L-50K-UH-BZ, NTF-A-NM-N4-3L-50K-UL-BZ, NTF-A-NM-N4-3L-57K-UH-BZ, NTF-A-NM-N4-3L-57K-UL-BZ, NTF-A-NM-N4-6L-30K-UH-BZ, NTF-A-NM-N4-6L-30K-UL-BZ, NTF-A-NM-N4-6L-40K-UH-BZ, NTF-A-NM-N4-6L-40K-UL-BZ, NTF-A-NM-N4-6L-50K-UH-BZ, NTF-A-NM-N4-6L-50K-UL-BZ, NTF-A-NM-N4-6L-57K-UH-BZ, NTF-A-NM-N4-6L-57K-UL-BZ, NTF-A-NM-N5-10L-30K-UH-BZ, NTF-A-NM-N5-10L-30K-UL-BZ, NTF-A-NM-N5-10L-40K-UH-BZ, NTF-A-NM-N5-10L-40K-UL-BZ, NTF-A-NM-N5-10L-50K-UH-BZ, NTF-A-NM-N5-10L-







**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-2ME-27L-XXXX-YY-ZZ-N-@@@-&&&-#### Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type , it can be blank or 20KV, &&&& indicate the amount of mounting bolt, it can be 4BLT or blank. #### indicate the shipping method, it can be blank or EXPD.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-2ME-30L-XXXX-YY-ZZ-N-@@@ Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type and the amount of mounting bolt, can be blank or 20KV,4BLT.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-3ME-22L-XXXX-YY-ZZ-N-@@@-&&&-#### Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type , it can be blank or 20KV, &&&& indicate the amount of mounting bolt, it can be 4BLT or blank. #### indicate the shipping method, it can be blank or EXPD.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-3ME-25L-XXXX-YY-ZZ-N-@@@ Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type and the amount of mounting bolt, can be blank or 20KV,4BLT.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-3ME-27L-XXXX-YY-ZZ-N-@@@-&&&-#### Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type , it can be blank or 20KV, &&&& indicate the amount of mounting bolt, it can be 4BLT or blank. #### indicate the shipping method, it can be blank or EXPD.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-3ME-30L-XXXX-YY-ZZ-N-@@@ Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type and the amount of mounting bolt, can be blank or 20KV,4BLT.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-4ME-22L-XXXX-YY-ZZ-N-@@@-&&&-#### Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type , it can be blank or 20KV, &&&& indicate the amount of mounting bolt, it can be 4BLT or blank. #### indicate the shipping method, it can be blank or EXPD.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-4ME-25L-XXXX-YY-ZZ-N-@@@ Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type and the amount of mounting bolt, can be blank or 20KV,4BLT.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-4ME-27L-XXXX-YY-ZZ-N-@@@-&&&-#### Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type , it can be blank or 20KV, &&&& indicate the amount of mounting bolt, it can be 4BLT or blank. #### indicate the shipping method, it can be blank or EXPD.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-4ME-30L-XXXX-YY-ZZ-N-@@@ Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type and the amount of mounting bolt, can be blank or 20KV,4BLT.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-5ME-22L-XXXX-YY-ZZ-N-@@@-&&&-#### Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type , it can be blank or 20KV, &&&& indicate the amount of mounting bolt, it can be 4BLT or blank. #### indicate the shipping method, it can be blank or EXPD.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-5ME-25L-XXXX-YY-ZZ-N-@@@ Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type and the amount of mounting bolt, can be blank or 20KV,4BLT.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-5ME-27L-XXXX-YY-ZZ-N-@@@-&&&-#### Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type , it can be blank or 20KV, &&&& indicate the amount of mounting bolt, it can be 4BLT or blank. #### indicate the shipping method, it can be blank or EXPD.

**LED Surface Mounted Luminaire**, Model(s) TRVXL-A-HT-5ME-30L-XXXX-YY-ZZ-N-@@@ Where XXXX indicate color temperature, can be 27K7,30K7, 40K7, 57K7. YY indicate input voltage, can be UL means 120-277V or UH means 347-480V. ZZ indicate product color, can be GY, BK, BZ. @@@@ indicate SPD type and the amount of mounting bolt, can be blank or 20KV,4BLT.

**LED Surface Mounted Luminaire**, Model(s) XSP, XSPR, XSPSM

**LED Surface Mounted Luminaire, Suitable for damp locations**, Model(s) C-HB-A-L4F-07L-40K-WH, C-HB-A-L4F-07L-50K-WH, C-HB-A-L4F-14L-40K-WH, C-HB-A-L4F-20L-40K-WH, C-HB-A-L4F-20L-50K-WH, C-HB-A-L4F-28L-40K-WH, C-HB-A-L4F-28L-50K-WH

**LED Surface Mounted Luminaire, Suitable for Wet locations**, Model(s) C-FL-A-LCF-1L-30K-FT-DB, C-FL-A-LCF-1L-30K-YK-DB, C-FL-A-LCF-1L-40K-FT-DB, C-FL-A-LCF-1L-40K-YK-DB, C-FL-A-LCF-3L-30K-FT-DB, C-FL-A-LCF-3L-30K-YK-DB, C-FL-A-LCF-3L-40K-FT-DB, C-FL-A-LCF-3L-40K-YK-DB, C-FL-A-LCF-6L-30K-FT-DB, C-FL-A-LCF-6L-30K-YK-DB, C-FL-A-LCF-6L-40K-FT-DB, C-FL-A-LCF-6L-40K-YK-DB

**LED Surface Mounted Luminaire, Suitable for wet locations**, Model(s) C-WP-A-ARFC-LG-4L-30K-DB, C-WP-A-ARFC-LG-4L-40K-DB, C-WP-A-ARFC-LG-4L-50K-DB, C-WP-A-ARFC-LG-8L-30K-DB, C-WP-A-ARFC-LG-8L-40K-DB, C-WP-A-ARFC-LG-8L-50K-DB, C-WP-A-ARFC-SM-1L-30K-DB, C-WP-A-ARFC-SM-1L-40K-DB, C-WP-A-ARFC-SM-1L-50K-DB, C-WP-A-ARFC-SM-3L-30K-DB, C-WP-A-ARFC-SM-3L-40K-DB, C-WP-A-ARFC-SM-3L-50K-DB

**LED surface pole-mounted luminaire and suitable for Wet Locations, "RSWM"**, Model(s) RSWM

**LED surface pole-mounted luminaire and suitable for Wet Locations**, Model(s) BRSW Series, BRSWM, OSQ, OSQ Series., RSW Series

**LED Surface Pole-Mounted Luminaires, suitable for wet locations**, Model(s) C-AR-DD-3L-40K-GR May be added with suffix -xxW-yyK.

**LED Surface Pole-Mounted Luminaires, suitable for wet locations**, Model(s) C-AR-DD-3L-50K-GR May be added with suffix -xxW-yyK.

**LED surface-mounted luminaire, "Flat-panel Series"**, Model(s) FP14-40L-xxx-xxx (i), FP22-34L-xxx-xxx (i), FP22-50L-xxx-xxx (i), FP24-40L-xxx-xxx (i), FP24-50L-xxx-xxx (i)

**LED surface-mounted luminaire**, Model(s) C-AR-A-2LXD where X = any alpha numeric character.

**LED surface-mounted luminaire**, Model(s) C-AR-A-4LXD where X = any alpha numeric character.

**LED surface-mounted luminaire**, Model(s) C-FL-A-RC-2L-40K-DB May be added with suffix -xxW-yyK.

**LED surface-mounted luminaire**, Model(s) C-FL-A-RC-2L-40K-WH May be added with suffix -xxW-yyK.

**LED surface-mounted luminaire**, Model(s) C-FL-A-RC-3L-40K-DB, C-FL-A-RC-3L-40K-WH, C-FL-A-RC-3L-50K-DB

**LED surface-mounted luminaire**, Model(s) C-FL-B-RC-2L-40K May be followed by WH or DB to indicate color.

**LED surface-mounted luminaire**, Model(s) C-WM-A-WLCYX where X = any alpha numeric character.

**LED surface-mounted luminaire**, Model(s) C-WM-A-WLSPX where X = any alpha numeric character.

**LED surface-mounted luminaire**, Model(s) CRLE-20L, CRLE-22L, CRLE-31L, CRLE-32L-xxK-yyy-HD(c), CRLE-32L-xxK-yyy-zzzz(c), CRLE-40L-xxK-yyy-zzzz(c), CRLE-40L-xxK-yyy-HD(c), CRLE-40LHE-30K, CRLE-40LHE-35K, CRLE-40LHE-40K, CRLE-40LHE-50K, CRLE-50L, CS14, CS14-22L+, CS14-38L+, CS14-38LHE+, CS14-40LHE+, CS18, CS18-44L+, CS18-75L+(a), CS18-80L+, CS18-80LHE+(a), CS18-82LHE+, CXB-23L-40K-U-1-FF-xxx\*, CXB-23L-40K-U-2-FF-xxx\*, E-ALX where X = any alpha numeric character., E-LL6L3WUN[#], E-WC, E-WG, E-WR2L304U, E-WR4L504U, JB4-600L, JB6-650L, LS4-40L-xxK-y(d), LS8-80L-xxK-y(d)

**LED surface-mounted luminaire**, Model(s) LSw4-40L-xxK-y(d) where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED surface-mounted luminaire**, Model(s) LSw8-80L-xxK-y(d) where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED surface-mounted luminaire**, Model(s) LSw8C-100L-35K-34-y-FD where w can be any letter or blank, and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED surface-mounted luminaire**, Model(s) LSw8C-100L-40K-34-y-FD where w can be any letter or blank, and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED surface-mounted luminaire**, Model(s) LSw8C-100L-50K-34-y-FD where w can be any letter or blank, and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED surface-mounted luminaire**, Model(s) RL24-20L-xxK-zz(b), RL40-40L-xxK-zz(b), S-FLCLX, S-FLCSX May be added with suffix -xxW-yyK., SL24-20L-xxK-zz(b), SL40-40L-xxK-zz(b)

**LED surface-mounted luminaire, Ceiling-Mounted**, Model(s) C-VT-A-STRP-47L-40K-WH, C-VT-A-STRP-47L-50K-WH

**LED surface-mounted luminaires, "E-conolight LED Commercial Wall Pack"**, Model(s) C-WP-A-TRX where X = any alpha numeric character., E-WP1L Series

**LED surface-mounted luminaires, "E-conolight LED Commercial Wall Pack"**, Model(s) E-WP1X Series where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Bullet Light"**, Model(s) C-FL-A-RDFX where X = any alpha numeric character.



**LED surface-mounted luminaires, "LED Bullet Light"**, Model(s) C-FL-A-RDSX where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Bullet Light"**, Model(s) E-GL, S-FLBSX where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Canopy Light"**, Model(s) C-CP-A-SQX where X = any alpha numeric character., E-CCX where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Canopy Light"**, Model(s) E-CSAXX where XX = any combination of numbers or numbers and letters.

**LED surface-mounted luminaires, "LED Flood Light"**, Model(s) C-FL-A-RTF1X where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Flood Light"**, Model(s) C-FL-A-RTF2X where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Flood Light"**, Model(s) C-FL-A-RTF4X where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Flood Light"**, Model(s) C-FL-A-RTS1X where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Flood Light"**, Model(s) C-FL-A-RTS2X where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Flood Light"**, Model(s) C-FL-A-RTS4X where X = any alpha numeric character.

**LED surface-mounted luminaires, "LED Flood Light"**, Model(s) E-FFAXX where XX = any combination of numbers or numbers and letters.

**LED surface-mounted luminaires, "LED Flood Light"**, Model(s) E-HLX where X = any alpha numeric character., S-FLGLX where X = any alpha numeric character., S-FLGSX where X = any alpha numeric character.

**LED surface-mounted luminaires, "Round Area Light"**, Model(s) ARE-EDR, BXAR, FLD-EDR, XAR

**LED surface-mounted luminaires, "Street Light or Area Light Series"**, Model(s) ARE-EDG, BXAL, FLD-EDG, XAL

**LED surface-mounted luminaires**, Model(s) ARE-SLM66, BX6A, BX6S, BXAB Series, BXABG Series, BXAK or XAK Series and TSP-EHO or HBY-EHO Series, BXAK, XAK, ARE-EHO or FLD-EHO Series, BXAKx Series, BXAL Series, BXALS Series, BXBN or XBN LED Series, BXBP or XBP and PWY-EDG LED Series, BXCP, BXCP9 or XCP9 or PKG-304 Series, BXCP9143\$, BXCP9144\$, BXCP9155\$, BXCP9159\$, BXCR9016, BXCR9017 (30 LED), BXCR9018 (20 LED), BXCR9019 (10 LED), BXCR9020, BXCR9021, BXCR9029, BXFR or XFR or FLD-OL Series, BXHC or XHC LED Series, BXHR, XHR or INT-EDR Series, BXPS or XPS or PKG-EDG Parking Structure Series, BXPS or XPS or TSP-EDG - Transportation Series, BXSP or XSP Series, BXSP Series (XSP Series), BXSP9007NY&, BXSP1, BXSP2, BXSPR Series, BXSPRx0, BXUC Series LED Undercabinet Light, C-AR-A-SL3-10L-50K-UH-3PC-DB, C-AR-A-SL3-10L-50K-UL-3PC-DB, C-AR-A-SL3-16L-30K-UH-3PC-DB, C-AR-A-SL3-16L-30K-UL-3PC-DB, C-AR-A-SL3-18L-40K-UH-3PC-DB, C-AR-A-SL3-18L-40K-UL-3PC-DB, C-AR-A-SL3-18L-50K-UH-3PC-DB, C-AR-A-SL3-18L-50K-UL-3PC-DB, C-AR-A-SL3-27L-30K-UH-3PC-DB, C-AR-A-SL3-27L-30K-UL-3PC-DB, C-AR-A-SL3-30L-40K-UH-3PC-DB, C-AR-A-SL3-30L-40K-UL-3PC-DB, C-AR-A-SL3-30L-50K-UH-3PC-DB, C-AR-A-SL3-30L-50K-UL-3PC-DB, C-AR-A-SL3-9L-30K-UH-3PC-DB, C-AR-A-SL3-9L-30K-UL-3PC-DB, C-AR-A-SL3-9L-40K-UH-3PC-DB, C-AR-A-SL3-9L-40K-UL-3PC-DB, C-AR-A-SL4-10L-50K-UH-3PC-DB, C-AR-A-SL4-16L-30K-UH-3PC-DB, C-AR-A-SL4-16L-30K-UL-3PC-DB, C-AR-A-SL4-18L-40K-UH-3PC-DB, C-AR-A-SL4-18L-40K-UL-3PC-DB, C-AR-A-SL4-18L-50K-UH-3PC-DB, C-AR-A-SL4-18L-50K-UL-3PC-DB, C-AR-A-SL4-28L-30K-UH-3PC-DB, C-AR-A-SL4-28L-30K-UL-3PC-DB, C-AR-A-SL4-30L-40K-UH-3PC-DB, C-AR-A-SL4-30L-40K-UL-3PC-DB, C-AR-A-SL4-30L-50K-UH-3PC-DB, C-AR-A-SL4-30L-50K-UL-3PC-DB, C-AR-A-SL4-9L-30K-UH-3PC-DB, C-AR-A-SL4-9L-30K-UL-3PC-DB, C-AR-A-SL4-9L-40K-UH-3PC-DB, C-AR-A-SL4-9L-40K-UL-3PC-DB, C-AR-A-SL5-10L-40K-UH-3PC-DB, C-AR-A-SL5-10L-40K-UL-3PC-DB, C-AR-A-SL5-10L-50K-UH-3PC-DB, C-AR-A-SL5-10L-50K-UL-3PC-DB, C-AR-A-SL5-16L-30K-UH-3PC-DB, C-AR-A-SL5-16L-30K-UL-3PC-DB, C-AR-A-SL5-18L-40K-UH-3PC-DB, C-AR-A-SL5-18L-40K-UL-3PC-DB, C-AR-A-SL5-18L-50K-UH-3PC-DB, C-AR-A-SL5-18L-50K-UL-3PC-DB, C-AR-A-SL5-28L-30K-UH-3PC-DB, C-AR-A-SL5-28L-30K-UL-3PC-DB, C-AR-A-SL5-31L-40K-UH-3PC-DB, C-AR-A-SL5-31L-40K-UL-3PC-DB, C-AR-A-SL5-31L-50K-UH-3PC-DB, C-AR-A-SL5-31L-50K-UL-3PC-DB, C-AR-A-SL5-9L-30K-UH-3PC-DB, C-AR-A-SL5-9L-30K-UL-3PC-DB, C-HB-A-RD-13L-40K-UH-WH, C-HB-A-RD-13L-40K-UL-WH, C-HB-A-RD-13L-50K-UH-WH, C-HB-A-RD-13L-50K-UL-WH, C-HB-A-RD-20L-40K-UH-WH, C-HB-A-RD-20L-40K-UL-WH, C-HB-A-RD-20L-50K-UH-WH, C-HB-A-RD-20L-50K-UL-WH, C-HB-A-RD-30L-40K-UH-WH, C-HB-A-RD-30L-40K-UL-WH, C-HB-A-RD-30L-50K-UH-WH, C-HB-A-RD-30L-50K-UL-WH, C-HB-A-RD-7L-40K-UH-WH, C-HB-A-RD-7L-40K-UL-WH, C-HB-A-RD-7L-50K-UH-WH, C-HB-A-RD-7L-50K-UL-WH, C-HB-A-RDAL-14L-40K-WH, C-HB-A-RDAL-14L-50K-WH, C-HB-A-RDAL-18L-40K-WH, C-HB-A-RDAL-18L-50K-WH, C-HB-A-RDAL-26L-40K-WH, C-HB-A-RDAL-26L-50K-WH, C-HB-A-RDPC-14L-40K-WH, C-HB-A-RDPC-14L-50K-WH, C-HB-A-RDPC-18L-40K-WH, C-HB-A-RDPC-18L-50K-WH, C-HB-A-RDPC-26L-40K-WH, C-HB-A-RDPC-26L-50K-WH, C-WM-A-WLSL-14L-50K-MB, C-WP-A-FCT3X, CPY250, CS14-38L(a), CS14-40LHE(a), E-FFAXX or S-FLGSX or FLGL Series Flood Light, E-FFAXX or S-FLGSX or S-FLGLX Series Flood lights, E-FFTAXX Series

**LED surface-mounted luminaires**, Model(s) E-GL Series LED Bullet Light where X = any alpha numeric character and XX = any combination of numbers or numbers and letters.

**LED surface-mounted luminaires**, Model(s) E-HLX Series LED Flood Light where X = any alpha numeric character and XX = any combination of numbers or numbers and letters.

**LED surface-mounted luminaires**, Model(s) E-HTH07A-HK40UXX Where XX represents accessory option for Fixture Color W = White, B = Black.

**LED surface-mounted luminaires**, Model(s) E-HTH07A-HK50UXX Where XX represents accessory option for Fixture Color W = White, B = Black.

**LED surface-mounted luminaires**, Model(s) E-HTH13A-HK40UXX Where XX represents accessory option for Fixture Color W = White, B = Black.

**LED surface-mounted luminaires**, Model(s) E-HTH13A-HK50UXX Where XX represents accessory option for Fixture Color W = White, B = Black.

**LED surface-mounted luminaires**, Model(s) E-HTH20A-HK40UXX Where XX represents accessory option for Fixture Color W = White, B = Black.

**LED surface-mounted luminaires**, Model(s) E-HTH20A-HK50UXX Where XX represents accessory option for Fixture Color W = White, B = Black.

**LED surface-mounted luminaires**, Model(s) E-HTH30A-HK40UXX Where XX represents accessory option for Fixture Color W = White, B = Black.

**LED surface-mounted luminaires**, Model(s) E-HTH30A-HK50UXX Where XX represents accessory option for Fixture Color W = White, B = Black.

**LED surface-mounted luminaires**, Model(s) E-SL3L131W, E-SL3L131WP, E-UN08L0321, E-UN13L0621, E-UN22L0921, E-UN30L1121, E-UN40L1521, E-WFCXX

**LED surface-mounted luminaires**, Model(s) E-WFTXX or S-WPT1X or S-WPT2X LED Series Wall Pack

**LED surface-mounted luminaires**, Model(s) E-WPX Series LED Wall Pack, E-WR1L383U, E-WR1L384U, EG series or WS series, FLD-304, HCD LED Series, HCF LED Series, KXS Series, LED Surface Mount Canopy Light, LED Yoke Mount Luminaire, LEDway BXIL Solar or XIL Solar, LEDway BXSL Solar or XSL Solar, LS Series - LED Wall Sconce, LS4-100L-xxK-y-FD, LS4-25L-xxK-y(d), LS4-40L-xxK-34-y(d), LS4-80L-xxK-y-FD, LS8-80L-xxK-34-y(d)

**LED surface-mounted luminaires**, Model(s) LSw4-25L-xxK-y(d) where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED surface-mounted luminaires**, Model(s) LSw4-25L-xxK-y-FD

**LED surface-mounted luminaires**, Model(s) LSw4-40L-xxK-34-y(d) where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED surface-mounted luminaires**, Model(s) LSw4-40L-xxK-y-FD, LSw4-50L-xxK-y-FD

**LED surface-mounted luminaires**, Model(s) LSw8-80L-xxK-34-y(d) where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**LED surface-mounted luminaires**, Model(s) PKG-304, RUL SERIES, S-CNP1X where X = any alpha numeric character.

**LED surface-mounted luminaires**, Model(s) S-FLBSX Series LED Bullet Light where X = any alpha numeric character and XX = any combination of numbers or numbers and letters.

**LED surface-mounted luminaires**, Model(s) S-WPCSX or S-WPCLX Series LED Wall Pack, STR-SLM66, X6A, X6S, XA-CR9010, XA-CR9013, XA-CR9014, XA-CR9015, XA-CR9016, XA-CR9017, XAB Series, XABG Series, XAL Series, XALS Series, XCC or BXCC Series, XCP, XCP9143\$, XCP9144\$, XSE or BXSE or SEC-EDG Series - LED Wall Pack, XSPLG, XSPMD, XSPx0

**LED Surface-mounted Luminaires, suitable for wet locations**, Model(s) C-FL-A-RDM-4L-50K-DB, C-FL-A-RDM-8L-40K-DB, C-FL-A-RDM-8L-50K-DB, C-FL-A-RDN-3L-40K-DB, C-FL-A-RDN-4L-50K-DB, C-FL-A-RDW-7L-40K-DB, C-FL-A-RDW-7L-50K-DB

**LED Surface-Mounted Luminaires, suitable for wet locations**, Model(s) C-WM-A-WLHO-34L-40K-MB, C-WM-A-WLHO-36L-50K-MB, C-WP-A-TRFC-6L-40K-DB, C-WP-A-TRFC-6L-50K-DB

**LED Wall Mount Luminaire**, Model(s) AL-40x Series, BXAL-40x Series, E-WPX(e) Series, LFL or RS Series or BXLFL Series, RS9062x Series, XAL-40x Series

**LED Yoke Mount Luminaire**, Model(s) VG, XVG or BXVG Series

**Light Emitting Diode, Surface Mount Luminaires**, Model(s) CE-JB4-xxxL-yyK-E26-2, CE-JB6-xxxL-yyK-E26-2, DDS4, DDS6

**Light Emitting Diode, Surface-Mounted Luminaire, suitable for ceiling mount, wall mount and suitable for Wet Locations**, Model(s) C-FL-A-RDC-1L-40K-BK, C-FL-A-RDC-1L-40K-WH

**Light-emitting-diode Luminaires, Pendant-Mounted**, Model(s) LN4-xxL-xxK-10V and may be followed by (-D80), where "xx" can be any number.

**Light-emitting-diode Luminaires, Pendant-Mounted**, Model(s) LN4-xxL-xxK-CMA and may be followed by (-D80), where "xx" can be any number.

**Light-emitting-diode Luminaires, Surface-Mounted**, Model(s) LS4-50L-xxK-y, LS8-100L-xxK-y

**Light-emitting-diode Luminaires, Surface-Mounted**, Model(s) LSw4-50L-xxK-y where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**Light-emitting-diode Luminaires, Surface-Mounted**, Model(s) LSw8-100L-xxK-y where w can be any letter or blank, xx can be any number and y can be S or 10V or blank. Model numbers may be preceded or followed by additional alpha-numeric characters which represent non-safety related features for marketing purposes only.

**Light-emitting-diode Luminaires, Surface-Mounted. Dimmable models, Suitable for damp location**, Model(s) C-PHB-A-L2F-13L-40K-WH, C-PHB-A-L2F-13L-50K-WH, C-PHB-A-L2F-20L-40K-WH, C-PHB-A-L2F-20L-50K-WH, C-PHB-A-L4F-27L-40K-WH, C-PHB-A-L4F-27L-50K-WH, E-HLD13A-HK#0UW (j), E-HLD20A-HK#0UW (j), E-HLD27A-HK#0UW (j)

**Light-emitting-diode Surface Mounted Luminaire, "IG Series"**, Model(s) IG-xx-xx-xYYK-ZZ-xx-xxx (h)

**Light-emitting-diode Surface Mounted Luminaire**, Model(s) HXBx where x = any combination of additional alpha-numeric characters

**Light-emitting-diode Surface-Mounted Luminaire, "series"**, Model(s) BXSPW, XSPW

**Light-emitting-diode Surface-Mounted Luminaire**, Model(s) BBD, BBD-LWY or BXBBB Series, BDPTx(f), BXSPW Series

**Light-emitting-diode Surface-Mounted Luminaire**, Model(s) C-VT-A-LGCLX where X = any alpha numeric character.

**Light-emitting-diode Surface-Mounted Luminaire**, Model(s) C-VT-A-LGPDx where X = any alpha numeric character.

**Light-emitting-diode Surface-Mounted Luminaire**, Model(s) C-VT-A-LGWLX where X = any alpha numeric character.

**Light-emitting-diode Surface-Mounted Luminaire**, Model(s) C-VT-A-SMCLX where X = any alpha numeric character.

**Light-emitting-diode Surface-Mounted Luminaire**, Model(s) C-VT-A-SMPDX where X = any alpha numeric character.

**Light-emitting-diode Surface-Mounted Luminaire**, Model(s) C-VT-A-SMWLX where X = any alpha numeric character.

**Light-emitting-diode Surface-Mounted Luminaire**, Model(s) DPTx(f), E-VT SERIES, LN Series, STRLWY, STR-LWY, XSTRLWY or BXSTRLWY Series, XSPW Series

**None**, Model(s) C-FL-A-RDM-3L-40K-DB, C-FL-A-RDW-3L-40K-DB, C-FL-A-RDW-3L-50K-DB

**Surface Pole Mount LED Luminaires**, Model(s) BXIL, BXUL, LEDWAY LED SERIES BXSL, XSL or STR-LWY, LEDWAY LED SERIES BXSLG, XSLG or BBD-LWY, STR-LWY-XX-XX-XX-X-XX-XX-XXX-IP, STR-LWY-XX-XX-XX-X-XX-XX-XXX-UTL, XIL, XUL

Model(s) LEDWay ECOSLM - STR-SLM, BXSS or XSS Series

# - Followed by #, which could be 0 through 9, indicating LED CCT

(a) - With or without "-CMA" denoting Cree SmartCast Option.

(b) - Where xx and zz are any alphanumeric combination not related to safety.

(c) - Where xx, yyy, and zzzz are any alphanumeric combination not related to safety.

(d) - Where xx can be any number and "y" can be S or 10V or blank.

(e) - Where X = 8 or 9.

(f) - where x = up to 15 additional alpha-numeric characters.

(h) - Where x can be any alpha numeric character, YY may be any two digit number, representing LED color temperature, and ?ZZ? may be ?UL? or ?34? representing input voltage of 120-277 or 347 volts respectively.

(i) - Where x can be any alpha numeric character that does not affect safety

(j) - Where # represents 0 thru 9 or A thru Z, which is used for distinction of different color temperatures and color rendering index.

\* - Where FF can be HC represents Hook and cord, PD represents pendant, DM represents direct mount, and TR represents Trunnion; JP represents Junction Box Pendant; and where xxx can be any alphanumeric.

+ - Maybe followed by "-2CT" denoting 2 circuit option

Trademark and/or Tradename: "CREE" , "E-Conolight" ,  ,  ,  , 

Last Updated on 2019-07-02

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission

from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"