













Stylus™ LED Recessed Specification Grade Luminaire

Delivered Lumens & Electrical Data*								
Length	Lumen Package	System Watts 120-347V	Initial Delivered Lumens**	Total Current (A)				
				120V	208V	240V	277V	347V
58'	L	256	23,200	2.16	1.24	1.07	0.93	0.73
	M	416	37,700	3.46	1.99	1.73	1.50	1.18
	H	581	52,200	4.90	2.78	2.41	2.09	1.67
60'	L	264	24,000	2.23	1.28	1.11	0.96	0.75
	M	429	39,000	3.57	2.06	1.78	1.54	1.21
	H	601	54,000	5.07	2.88	2.49	2.16	1.73
62'	L	272	24,800	2.30	1.32	1.14	0.99	0.78
	M	443	40,300	3.69	2.12	1.84	1.59	1.25
	H	620	55,800	5.23	2.97	2.57	2.23	1.78
64'	L	280	25,600	2.37	1.36	1.18	1.02	0.80
	M	456	41,600	3.80	2.18	1.89	1.64	1.28
	H	640	57,600	5.40	3.06	2.65	2.30	1.84
66'	L	291	26,400	2.46	1.41	1.22	1.06	0.83
	M	473	42,900	3.94	2.26	1.96	1.70	1.34
	H	661	59,400	5.58	3.17	2.75	2.38	1.90
68'	L	299	27,200	2.53	1.45	1.25	1.09	0.85
	M	486	44,200	4.05	2.33	2.02	1.75	1.38
	H	681	61,200	5.75	3.26	2.83	2.45	1.94
70'	L	307	28,000	2.60	1.49	1.29	1.12	0.87
	M	500	45,500	4.16	2.39	2.08	1.80	1.41
	H	700	63,000	5.91	3.32	2.91	2.50	1.97
72'	L	315	28,800	2.67	1.53	1.33	1.15	0.90
	M	513	46,800	4.28	2.46	2.15	1.85	1.45
	H	720	64,800	6.08	3.44	2.99	2.57	2.07

\* Electrical data at 25°C (77°F). Actual wattage may differ +/- 10% when operating between 120V and 347V +/- 10%  
 \*\* Initial delivered lumens at 25°C (77°F). Actual product yield may vary +/- 10% from -10% to +10% of initial delivered lumens