

### CAUTIONS

#### IMPORTANT SAFEGUARDS

When using electrical equipment, basic safety precautions should always be followed including the following:


#### READ AND FOLLOW ALL SAFETY INSTRUCTIONS

1. To reduce the risk of electrical shock, turn off power supply before installation or servicing.
2. This luminaire must be installed in accordance with the NEC and your local electrical code. If you are not familiar with these codes and requirements, consult a qualified electrician.
3. When tightening Allen head set screws, make sure to tighten in a crossing pattern. Do not tighten adjacent screws proceeding around the hub. Make sure all screws are “snug” before tightening to 120 in.lbs (13 N-m).
4. Strain relief is required for electrical connections at heights of 25' (7.6 m) and above. Knot the supply wires from the pole with the fixture cord inside the cast hub.

#### SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE

### TO INSTALL:

(CROSS PATTERN TIGHTENING METHOD)



F1

#### SET SCREW TIGHTENING

##### STEP 1:

Using 3/16" allen wrench, tighten eight (8) allen head set screws in a crossing pattern around tenon until all are snug. (Do not fully tighten) See **Figure 1**.

##### STEP 2:

Torque set screws to 120 in.lbs (13 N-m). See **Figure 2**.

Cast hub



F2