















**Field Adjustable Output (Q8/Q7/Q6/Q5/Q4/Q3/Q2/Q1) Option Description:**

The Field Adjustable Output option enables the street and area luminaire within the RSW Series on this page to be tuned to the exact needs of a particular application through multiple levels of adjustment. When ordered with the Q option, the luminaire will be shipped from the factory at the selected lumen output, will be fully adjustable between the outputs, and will include a wattage label that indicates the wattage of the luminaire at the selected lumen output (Rounded to nearest 10 watts per ANSI C136.15-2015.). Additional dimming functionality is available when a dimming control (by others) is used in the 7-Pin receptacle.

**Locked Lumen Output (X7/X6/X5/X4/X3/X2/X1) Option Description:**

The Locked Lumen Output option on this page permanently locks the lumen output on the RSW Series street and area luminaire to the setting selected. When ordered with the X option, the luminaire will be shipped from the factory at the lumen output setting selected, and will include a wattage label that indicates the wattage of the setting selected. When this option is selected, the luminaire output is not able to be adjusted in the field except if a dimming control (by others) is used in the 7-Pin receptacle.

**Q & X Option Power & Lumen Data – 9L**

Q Option Setting	X Option Setting	CCT/CRI	System Watts <sup>†</sup>		Lumen Values <sup>†</sup>		Output	
			120-277V	Label Wattage	2LG, 2ME & 3ME	w/BLS	Standard	Premium
Q4	X4	27K8	65	70	6,800	6,250	2LG, 2ME, 3ME	
		30K7	65	70	7,750	7,125		2LG, 2ME, 3ME
		30K8	65	70	7,225	6,625	2LG, 2ME, 3ME	
		40K7	62	60	7,750	7,125		2LG, 2ME, 3ME
		40K8	65	70	7,650			2LG, 2ME, 3ME
		50K7	61	60	7,750	7,125		2LG, 2ME, 3ME
		50K8	63	60	7,750	7,125		2LG, 2ME, 3ME
Q3	X3	27K8	61	60	6,400	6,000	2LG, 2ME, 3ME	
		30K7	61	60	7,300	6,750		2LG, 2ME, 3ME
		30K8	61	60	6,825	6,275	2LG, 2ME, 3ME	
		40K7	59	60	7,750	7,125		2LG, 2ME, 3ME
		40K8	61	60	7,200	6,600		2LG, 2ME, 3ME
		50K7	58	60	7,750	6,700		2LG, 2ME, 3ME
		50K8	60	60	7,300	6,700		2LG, 2ME, 3ME
Q2	X2	27K8	60	60	6,125	5,625	2LG, 2ME, 3ME	
		30K7	60	60	6,900	6,425		2LG, 2ME, 3ME
		30K8	60	60	6,525	6,000	2LG, 2ME, 3ME	
		40K7	56	60	7,000	6,425		2LG, 2ME, 3ME
		40K8	60	60	6,900	6,325	2LG, 2ME, 3ME	
		50K7	56	60	7,000	6,425		2LG, 2ME, 3ME
		50K8	58	60	7,000	6,425		2LG, 2ME, 3ME
Q1	X1	27K8	50	50	5,700	5,225	2LG, 2ME, 3ME	
		30K7	50	50	6,500	5,975		2LG, 2ME, 3ME
		30K8	50	50	6,050	5,550	2LG, 2ME, 3ME	
		40K7	48	50	6,500	5,975		2LG, 2ME, 3ME
		40K8	50	50	6,400	5,875		2LG, 2ME, 3ME
		50K7	47	50	6,500	5,975		2LG, 2ME, 3ME
		50K8	49	50	6,500	5,975		2LG, 2ME, 3ME

<sup>†</sup> Electrical and lumen output is at 25°C (77°F). Actual wattage and lumen output may differ by +/-10% when operating between 120-277V +/-10%