

# IFAO7.E333790 - Light-emitting-diode Recessed Luminaires Certified for Canada

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please refer to the Certificate of Compliance or contact our Customer Service at <https://www.ul.com/about/locations>.

## Light-emitting-diode Recessed Luminaires Certified for Canada

### Ideal Industries Lighting LLC, dba Cree Lighting

E333790

4401 Silicon Drive  
Durham, NC 27703 United States

Trademark and/or Tradename:  ,  ,  ,  ,  
 , 

Note: For additional marking information, refer to the [Guide Information Page](#).

Model(s): RC4, RC4-GU24, RR4-GU24

Model(s): E-TDF03E-22RXXN where (x) can be any alpha numeric character that does not affect safety.

Model(s): E-TDF04E-14RXXN where (x) can be any alpha numeric character that does not affect safety.

Model(s): E-TDF04E-24RXXN where (x) can be any alpha numeric character that does not affect safety.

Model(s): E-TDF05E-22RXXN where (x) can be any alpha numeric character that does not affect safety.

Model(s): E-TDF05E-24RXXN where (x) can be any alpha numeric character that does not affect safety.

Model(s): RC6 may be followed by additional suffixes for commercial purposes.

Model(s): RC6-GU24 may be followed by additional suffixes for commercial purposes.

Model(s): RR6 may be followed by additional suffixes for commercial purposes.

Model(s): RR6-GU24 may be followed by additional suffixes for commercial purposes.

**LED recessed luminaire**, Model(s): C-TR-B-BT14-S42L-SCCT-UL-WH, C-TR-B-BT14-S42L-SCCT-UL-WH-EB, C-TR-B-BT22-S40L-SCCT-UL-WH, C-TR-B-BT22-S40L-SCCT-UL-WH-EB, C-TR-B-BT22-S55L-SCCT-UL-WH, C-TR-B-BT22-S55L-SCCT-UL-WH-EB, C-TR-B-BT24-S47L-SCCT-UL-WH, C-TR-B-BT24-S47L-SCCT-UL-WH-EB, C-TR-B-BT24-S67L-SCCT-UL-WH, C-TR-B-BT24-S67L-SCCT-UL-WH-EB, C-TR-C-FP14-31L-35K-WH, C-TR-C-FP14-31L-35K-WH-EB, C-TR-C-FP14-31L-40K-WH, C-TR-C-FP14-31L-40K-WH-EB, C-TR-C-FP14-31L-50K-WH, C-TR-C-FP14-31L-50K-WH-EB, C-TR-C-FP14-37L-35K-WH, C-TR-C-FP14-37L-35K-WH-EB, C-TR-C-FP14-37L-40K-WH, C-TR-C-FP14-37L-40K-WH-EB, C-TR-C-FP14-37L-50K-WH, C-TR-C-FP14-37L-50K-WH-EB, C-TR-C-FP14-42L-30K-WH, C-TR-C-FP14-50L-35K-WH, C-TR-C-FP14-50L-35K-WH-EB, C-TR-C-FP14-50L-40K-WH, C-TR-C-FP14-50L-40K-WH-EB, C-TR-C-FP14-50L-50K-WH, C-TR-C-FP14-50L-50K-WH-EB, C-TR-C-FP22-25L-35K-WH, C-TR-C-FP22-25L-35K-WH-EB, C-TR-C-FP22-25L-40K-WH, C-TR-C-FP22-25L-40K-WH-EB, C-TR-C-FP22-25L-50K-WH, C-TR-C-FP22-25L-50K-WH-EB, C-TR-C-FP22-31L-30K-WH, C-TR-C-FP22-31L-30K-WH-EB, C-TR-C-FP22-31L-35K-WH, C-TR-C-FP22-31L-35K-WH-EB, C-TR-C-FP22-31L-40K-WH, C-TR-C-FP22-31L-40K-WH-EB, C-TR-C-FP22-31L-50K-WH, C-TR-C-FP22-31L-50K-WH-EB, C-TR-C-FP22-37L-35K-WH, C-TR-C-FP22-37L-35K-WH-EB, C-TR-C-FP22-37L-40K-WH, C-TR-

C-FP22-37L-40K-WH-EB, C-TR-C-FP22-37L-50K-WH, C-TR-C-FP22-37L-50K-WH-EB, C-TR-C-FP22-42L-30K-WH, C-TR-C-FP22-42L-30K-WH-EB, C-TR-C-FP22-45L-35K-WH, C-TR-C-FP22-45L-35K-WH-EB, C-TR-C-FP22-45L-40K-WH, C-TR-C-FP22-45L-40K-WH-EB, C-TR-C-FP22-45L-50K-WH, C-TR-C-FP22-45L-50K-WH-EB, C-TR-C-FP22-55L-30K-WH-EB, C-TR-C-FP24-37L-35K-WH, C-TR-C-FP24-37L-35K-WH-EB, C-TR-C-FP24-37L-40K-WH, C-TR-C-FP24-37L-40K-WH-EB, C-TR-C-FP24-37L-50K-WH, C-TR-C-FP24-37L-50K-WH-EB, C-TR-C-FP24-50L-35K-WH, C-TR-C-FP24-50L-35K-WH-EB, C-TR-C-FP24-50L-40K-WH, C-TR-C-FP24-50L-40K-WH-EB, C-TR-C-FP24-50L-50K-WH, C-TR-C-FP24-50L-50K-WH-EB, C-TR-C-FP24-52L-30K-WH, C-TR-C-FP24-52L-30K-WH-EB, C-TR-C-FP24-62L-35K-WH, C-TR-C-FP24-62L-35K-WH-EB, C-TR-C-FP24-62L-40K-WH, C-TR-C-FP24-62L-40K-WH-EB, C-TR-C-FP24-62L-50K-WH, C-TR-C-FP24-62L-50K-WH-EB, ZR14-30L-830-10V5-34, ZR14-30L-830-10V5-UNV, ZR14-30L-830-10V5-UNV-EB, ZR14-30L-835-10V5-34, ZR14-30L-835-10V5-UNV, ZR14-30L-835-10V5-UNV-EB, ZR14-30L-840-10V5-34, ZR14-30L-840-10V5-UNV, ZR14-30L-840-10V5-UNV-EB, ZR14-30L-850-10V5-34, ZR14-30L-850-10V5-UNV, ZR14-30L-850-10V5-UNV-EB, ZR14-40L-830-10V5-34, ZR14-40L-830-10V5-UNV, ZR14-40L-830-10V5-UNV-EB, ZR14-40L-835-10V5-34, ZR14-40L-835-10V5-UNV, ZR14-40L-835-10V5-UNV-EB, ZR14-40L-840-10V5-34, ZR14-40L-840-10V5-UNV, ZR14-40L-840-10V5-UNV-EB, ZR14-40L-850-10V5-34, ZR14-40L-850-10V5-UNV, ZR14-40L-850-10V5-UNV-EB, ZR14-50L-830-10V5-34, ZR14-50L-830-10V5-UNV, ZR14-50L-830-10V5-UNV-EB, ZR14-50L-835-10V5-34, ZR14-50L-835-10V5-UNV, ZR14-50L-835-10V5-UNV-EB, ZR14-50L-840-10V5-34, ZR14-50L-840-10V5-UNV, ZR14-50L-840-10V5-UNV-EB, ZR14-50L-850-10V5-34, ZR14-50L-850-10V5-UNV, ZR14-50L-850-10V5-UNV-EB, ZR14-60L-830-10V5-34, ZR14-60L-830-10V5-UNV, ZR14-60L-830-10V5-UNV-EB, ZR14-60L-835-10V5-34, ZR14-60L-835-10V5-UNV, ZR14-60L-835-10V5-UNV-EB, ZR14-60L-840-10V5-34, ZR14-60L-840-10V5-UNV, ZR14-60L-840-10V5-UNV-EB, ZR14-60L-850-10V5-34, ZR14-60L-850-10V5-UNV, ZR14-60L-850-10V5-UNV-EB, ZR22-20L-830-10V5-34, ZR22-20L-830-10V5-UNV, ZR22-20L-830-10V5-UNV-EB, ZR22-20L-835-10V5-34, ZR22-20L-835-10V5-UNV, ZR22-20L-835-10V5-UNV-EB, ZR22-20L-840-10V5-34, ZR22-20L-840-10V5-UNV, ZR22-20L-840-10V5-UNV-EB, ZR22-20L-850-10V5-34, ZR22-20L-850-10V5-UNV, ZR22-20L-850-10V5-UNV-EB, ZR22-30L-830-10V5-34, ZR22-30L-830-10V5-UNV, ZR22-30L-830-10V5-UNV-EB, ZR22-30L-835-10V5-34, ZR22-30L-835-10V5-UNV, ZR22-30L-835-10V5-UNV-EB, ZR22-30L-840-10V5-34, ZR22-30L-840-10V5-UNV, ZR22-30L-840-10V5-UNV-EB, ZR22-30L-850-10V5-34, ZR22-30L-850-10V5-UNV, ZR22-30L-850-10V5-UNV-EB, ZR22-40L-830-10V5-34, ZR22-40L-830-10V5-UNV, ZR22-40L-830-10V5-UNV-EB, ZR22-40L-835-10V5-34, ZR22-40L-835-10V5-UNV, ZR22-40L-835-10V5-UNV-EB, ZR22-40L-840-10V5-34, ZR22-40L-840-10V5-UNV, ZR22-40L-840-10V5-UNV-EB, ZR22-40L-850-10V5-34, ZR22-40L-850-10V5-UNV, ZR22-40L-850-10V5-UNV-EB, ZR22-50L-830-10V5-34, ZR22-50L-830-10V5-UNV, ZR22-50L-830-10V5-UNV-EB, ZR22-50L-835-10V5-34, ZR22-50L-835-10V5-UNV, ZR22-50L-835-10V5-UNV-EB, ZR22-50L-840-10V5-34, ZR22-50L-840-10V5-UNV, ZR22-50L-840-10V5-UNV-EB, ZR22-50L-850-10V5-34, ZR22-50L-850-10V5-UNV, ZR22-50L-850-10V5-UNV-EB, ZR24-100L-830-10V5-34, ZR24-100L-830-10V5-UNV, ZR24-100L-830-10V5-UNV-EB, ZR24-100L-835-10V5-34, ZR24-100L-835-10V5-UNV, ZR24-100L-835-10V5-UNV-EB, ZR24-100L-840-10V5-34, ZR24-100L-840-10V5-UNV, ZR24-100L-840-10V5-UNV-EB, ZR24-100L-850-10V5-34, ZR24-100L-850-10V5-UNV, ZR24-100L-850-10V5-UNV-EB, ZR24-30L-830-10V5-34, ZR24-30L-830-10V5-UNV, ZR24-30L-830-10V5-UNV-EB, ZR24-30L-835-10V5-34, ZR24-30L-835-10V5-UNV, ZR24-30L-835-10V5-UNV-EB, ZR24-30L-840-10V5-34, ZR24-30L-840-10V5-UNV, ZR24-30L-840-10V5-UNV-EB, ZR24-30L-850-10V5-34, ZR24-30L-850-10V5-UNV, ZR24-30L-850-10V5-UNV-EB, ZR24-40L-830-10V5-UNV, ZR24-40L-830-10V5-UNV-EB, ZR24-40L-835-10V5-UNV, ZR24-40L-835-10V5-UNV-EB, ZR24-40L-840-10V5-UNV, ZR24-40L-840-10V5-UNV-EB, ZR24-50L-850-10V5-34, ZR24-60L-830-10V5-34, ZR24-60L-830-10V5-UNV, ZR24-60L-830-10V5-UNV-EB, ZR24-60L-835-10V5-34, ZR24-60L-835-10V5-UNV, ZR24-60L-835-10V5-UNV-EB, ZR24-60L-840-10V5-34, ZR24-60L-840-10V5-UNV, ZR24-60L-840-10V5-UNV-EB, ZR24-60L-850-10V5-34, ZR24-60L-850-10V5-UNV, ZR24-60L-850-10V5-UNV-EB, ZR24-70L-830-10V5-34, ZR24-70L-830-10V5-UNV, ZR24-70L-830-10V5-UNV-EB, ZR24-70L-835-10V5-34, ZR24-70L-835-10V5-UNV, ZR24-70L-835-10V5-UNV-EB, ZR24-70L-840-10V5-34, ZR24-70L-840-10V5-UNV, ZR24-70L-840-10V5-UNV-EB, ZR24-70L-850-10V5-34, ZR24-70L-850-10V5-UNV, ZR24-70L-850-10V5-UNV-EB, ZR24-80L-830-10V5-34, ZR24-80L-830-10V5-UNV, ZR24-80L-830-10V5-UNV-EB, ZR24-80L-835-10V5-34, ZR24-80L-835-10V5-UNV, ZR24-80L-835-10V5-UNV-EB, ZR24-80L-840-10V5-34, ZR24-80L-840-10V5-UNV, ZR24-80L-840-10V5-UNV-EB, ZR24-80L-850-10V5-34, ZR24-80L-850-10V5-UNV, ZR24-80L-850-10V5-UNV-EB

**LED recessed luminaire**, Model(s): CR14 Model number may be followed by -CP which indicates CCEA approval.

**LED recessed luminaire**, Model(s): CR22 Model number may be followed by -CP which indicates CCEA approval.

**LED recessed luminaire**, Model(s): CR24 Model number may be followed by -CP which indicates CCEA approval.

**LED recessed luminaire**, Model(s): FLX14-32L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.

**LED recessed luminaire**, Model(s): FLX14-32L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.

**LED recessed luminaire**, Model(s): FLX14-32L-xxK-34-CMA-FD with optional suffix -CP for Chicago Plenum.

**LED recessed luminaire**, Model(s): FLX14-32L-xxK-CMA-FD with optional suffix -CP for Chicago Plenum.

**LED recessed luminaire**, Model(s): FLX14-40L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.

- LED recessed luminaire**, Model(s): FLX14-40L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX14-40L-xxK-34-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX14-40L-xxK-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX14-50L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX14-50L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX14-50L-xxK-34-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX14-50L-xxK-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX14-60L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX14-60L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX22-20L-xxK-10V-FD-01 with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX22-32L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX22-32L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX22-32L-xxK-34-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX22-32L-xxK-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX22-50L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX22-50L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX22-50L-xxK-34-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX22-50L-xxK-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-32L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-32L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-32L-xxK-34-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-32L-xxK-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-40L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-40L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-40L-xxK-34-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-40L-xxK-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-50L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-50L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-50L-xxK-34-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-50L-xxK-CMA-FD with optional suffix -CP for Chicago Plenum.
- LED recessed luminaire**, Model(s): FLX24-60L-xxK-10V-FD with optional suffix -CP for Chicago Plenum.

**LED recessed luminaire**, Model(s): FLX24-60L-xxK-34-10V-FD with optional suffix -CP for Chicago Plenum.

**LED recessed luminaire**, Model(s): ZR14-30L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR14-40L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR14-50L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR14-60L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR14MT-40L-xxK-10V Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR14MT-40L-xxK-34-10V where xx represents 32 for 3200, 40 for 4000, or 50 for 5000 lumens.

**LED recessed luminaire**, Model(s): ZR14MT-40L-xxK-SC1 where xx represents 32 for 3200, 40 for 4000, or 50 for 5000 lumens.

**LED recessed luminaire**, Model(s): ZR14MT-50L-xxK-10V where xx represents 32 for 3200, 40 for 4000, or 50 for 5000 lumens.

**LED recessed luminaire**, Model(s): ZR14MT-50L-xxK-SC1 Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR22-20L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR22-30L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR22-40L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR22-50L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR22MT-32L-xxK-10V Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR22MT-32L-xxK-34-10V Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR22MT-32L-xxK-SC1 Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR22MT-40L-xxK-SC1 Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR22wT-40L-xxK-y-aa where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire**, Model(s): ZR24-100L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR24-30L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR24-40L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR24-50L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR24-60L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR24-70L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR24-80L-8bb-XXXX-UNV Where bb represents Temperature Color, it can be 30K, 35K, 40K, 50K. Where XXXX means representative control mode, Can be up to 4 alphanumeric characters.

**LED recessed luminaire**, Model(s): ZR24MT-40L-xxK-10V Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR24MT-40L-xxK-34-10V Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR24MT-50L-xxK-10V Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR24MT-50L-xxK-SC1 Where xx is any number times 100 in Kelvin

**LED recessed luminaire**, Model(s): ZR24w-50L-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire finishing section**, Model(s): LR6-277V+, LR6C-277V+, LR6C-DR1000-277V+, LR6C-DR650-277V+, LR6-DR1000-277V+, LR6-DR650-277V+

**LED recessed luminaire rough-in section**, Model(s): RC6-12W, RC6-12W-GU24, RC6-277V, RR6-12W, RR6-12W-GU24, RR6-277V

**LED recessed luminaire rough-in section, Type IC**, Model(s): H6-277V+, H6-GU24+, RC4-UNI, RC6-UNI, RR4, RR4-UNI, RR6-UNI

**LED recessed luminaire rough-in section, Type IC/Type Non-IC**, Model(s): LR22, LXR22

**LED recessed luminaire, Type IC**, Model(s): AR22-32L-xxK-y(@), AR24-40L-xxK-y(@), E-TR14L2403U, E-TR14L2404U, E-TR22L2383U, E-TR22L2384U, E-TR24L2503U, E-TR24L2504U, ST3-RC Series

**LED recessed luminaire, Type IC**, Model(s): ZR14w-40L-xxK-34-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR14w-40L-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR14w-40L-xxK-y-FD-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR14wC-40L-xxK-y-FD-aa where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR14wC-50L-xxK-y-FD-aa where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR14wT-40L-xxK-34-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR14wT-40L-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR14wT-50L-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR22w-32LHE-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR22w-32L-xxK-34-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR22w-32L-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR22w-32L-xxK-y-FD-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR22wC-32L-xxK-y-FD-aa where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR22wC-40L-xxK-y-FD-aa where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR22wT-32L-xxK-34-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR22wT-32L-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24w-40LHE-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24w-40L-xxK-34-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24w-40L-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24w-40L-xxK-y-FD-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24wC-40L-xxK-y-FD-aa where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24wC-50L-xxK-y-FD-aa where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24wT-40L-xxK-34-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24wT-40L-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24wT-40L-xxk-y-aa-FL where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC**, Model(s): ZR24wT-50L-xxK-y-aa\$ where w can be any letter or blank, xx can be any number, y can be S, 10V, CMA, or blank, and aa can be CP, any alphanumeric character or blank.

**LED recessed luminaire, Type IC, "Flat-panel Series"**, Model(s): FP14-40L-xxx-xxx (a), FP22-34L-xxx-xxx (a), FP22-50L-xxx-xxx (a), FP24-40L-xxx-xxx (a), FP24-50L-xxx-xxx (a)

**LED recessed luminaire, Type Non-IC**, Model(s): DLED-146-XX series#, DLED-166-YY series#, DLED-186-YY series#, DLED-8540-XX series (c), DLED-8560-XX series (c), DLED-8580-XX series (c)

# - Where XX can be 10W, 15W, 22W, 30W, 40W. Where YY can be 10W, 15W, 22W, 30W, 40W, 50W, 60W, 70W and 90W. Suitable for damp location.

\$ - Where w can be any letter or blank. xx can be any number. y can be S, 10V, CMA, or blank. and aa can be any alphanumeric character or blank.

(@) - Where xx can be any number and y can be S or 10V or LES or blank.

(a) - Where x can be any alpha numeric character that does not affect safety.

(c) - Where XX can be 15W, 23W, 30W, 40W. Suitable for damp location.

\* - May be provided with additional suffixes.

+ - Optional suffixes for marketing purposes.

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"