

# C-TR-B-FP24 Series

LED Flat Panel - 2' x 4'

Replaces 3 x F32T8



## LOW PROFILE DESIGN, EASY INSTALLATION, FULLY BACKED BY CREE LIGHTING

Reliable, versatile and stylish – that's C-Lite LED Flat Panels. C-Lite LED Flat Panels deliver brighter light and bigger savings, and are fully tested and backed by Cree Lighting!



## PRODUCT SPECIFICATIONS

### OVERVIEW

- Initial Delivered Lumens: 5,000
- CRI: 80
- CCT: Warm White 3500K, Neutral White 4000K, Cool White 5000K
- Mounting: Recessed
- Input Power: 50 Watts
- Dimmable: 0-10V Dimming to 10%
- Operating Range: -20°C (-4°F) - 40°C (104°)
- Lifespan: Estimated >100,000 Hours
- Power Factor: > 0.9
- Total Harmonic Distortion: < 20%
- Limited Warranty: 5-Years\*
- Replaces 3 x F32T8

| FEATURES  | BENEFITS   | RECOMMENDED USE   |
|---|--|---|
| <ul style="list-style-type: none"> <li>• Pre-installed driver</li> <li>• White powder coated aluminum frame</li> <li>• Opaque white acrylic lens</li> </ul> | <ul style="list-style-type: none"> <li>• IC Rated for direct contact with insulation</li> <li>• Fits in low-clearance drop ceilings</li> <li>• Fully tested and backed by Cree Lighting</li> </ul> | <ul style="list-style-type: none"> <li>• Offices</li> <li>• Educational &amp; Retail</li> <li>• Commercial &amp; Institutional</li> </ul> |

## ORDERING INFORMATION


Example: C-TR-B-FP24-50L-40K-WH-2

| C-TR    | B      | FP24                       | 50L                        |  | WH          |             |
|---------|--------|----------------------------|----------------------------|--|-------------|-------------|
| PRODUCT | SERIES | STYLE                      | LUMEN PACKAGE              | CCT  | COLOR       | PACKAGING   |
| C-TR    | B      | FP24<br>Flat Panel 2' x 4' | 50L<br>5,000 Lumens<br>50W | 35K<br>Warm White (3500K)<br>40K<br>Neutral White (4000K)<br>50K<br>Cool White (5000K) | WH<br>White | 2<br>2-Pack |

## CERTIFICATIONS



# C-TR-B-FP24 Series



## SERIES OVERVIEW

| DIMENSIONS   | PRODUCT WEIGHT | MOUNTING HEIGHT | SPACING             |
|--|----------------|-----------------|---------------------|
| 47.63" (1194mm) L x 23.63" (600mm) W x 0.5" (13mm) H (Panel)<br>47.63" (1194mm) L x 23.63" (600mm) W x 1.75" (44mm) H (w/Driver) | 14.4 lbs.      | 8 to 12 feet    | 8' x 8' – 10' x 10' |

## FIXTURE SPECIFICATIONS

|                      |   |
|----------------------|---|
| <b>HOUSING</b>       | Durable aluminum construction<br>White polyester powder-coat<br>Sealed, maintenance-free fixture design   |
| <b>LENS ASSEMBLY</b> | Precision engineered acrylic lens and polymethyl methacrylate (PMMA) diffuser prevents hot spots, shadows and glare, while providing uniform illumination |
| <b>MOUNTING</b>      | Recessed<br>Installs into conventional grid ceiling<br>Pre-installed driver<br>Requires minimum 90°C supply conductors                                    |

## ELECTRICAL PERFORMANCE

| OPERATING RANGE             | LIFESPAN<br>L <sub>70</sub> AT 25°C (77°F) | POWER FACTOR | TOTAL HARMONIC<br>DISTORTION | DIMMABLE             |
|-----------------------------|--|--------------|------------------------------|----------------------|
| -20°C (-4°F) - 40°C (104°F) | Estimated<br>>100,000 Hours                | > 0.9        | < 20%                        | 0-10V Dimming to 10% |
| <b>INPUT VOLTAGE</b>        | <b>120V</b>                                | <b>208V</b>  | <b>240V</b>                  | <b>277V</b>          |
| <b>CURRENT DRAW (Amps)</b>  | 0.42A                                      | 0.24A        | 0.21A                        | 0.18A                |

## WARRANTY & CERTIFICATIONS

| WARRANTY        | ETL LISTED                              | DLC   |
|-----------------|---|---|
| 5-Year Limited* | Damp Locations.<br>For indoor use only. | DLC Qualified<br>Please refer to<br><a href="http://www.designlights.org/QPL">www.designlights.org/QPL</a> for most current information |

**CA RESIDENTS WARNING** - Cancer and Reproductive Harm -  
[www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

US - [c-lite.com](http://c-lite.com) T (800) 236-6800 F (262) 504-5415

Canada - [creelighting-canada.com](http://creelighting-canada.com) T (800) 473-1234 F (800) 890-7507


Rev. Date: 02/17/2021

For informational purposes only. Content is subject to change. \*See [creelighting.com/warranty](http://creelighting.com/warranty) for details

**C-LITE**  
LED LIGHTING

# C-TR-B-FP24 Series

## ACCESSORIES

|   | DRYWALL GRID ADAPTER   |
|---|--|
|  | SKU: <b>DGA24-WHT</b> (single-pack)<br><b>DGA24-WHT-10PK</b> (10-pack)<br>USE: For use when mounting in drywall ceilings |

© 2021 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent [creelighting.com/patents](http://creelighting.com/patents). C-LITE® and the C-LITE logo are registered trademarks of Cree Lighting, A company of IDEAL INDUSTRIES. The ETL Listed Intertek logo is a trademark of Intertek Testing Services NA, Inc.

US • [c-lite.com](http://c-lite.com) T (800) 236-6800 F (262) 504-5415 Canada • [creelighting-canada.com](http://creelighting-canada.com) T (800) 473-1234 F (800) 890-7507

Rev. Date: 02/17/2021

For informational purposes only. Content is subject to change. \*See [creelighting.com/warranty](http://creelighting.com/warranty) for details

**C-LITE**  
LED LIGHTING